

Replacement Blade Instructions



All-In-One Replacement Blade with Jacket Strip Blade

Each replacement blade package includes the following:

Qty	Description	Application
1	Strip/Core Blade	Cores dielectric foam and strips back aluminum sheath.
2	10-32 x 5/8" Button Head Screw	1 Installs the SC blade in the "A" housing at large center hole. 1 installs jacket strip blade in "B" housing.
1	1/8" Short Arm Hex Key	For all button head screw installations.
1	3/32" Short Arm Hex Key	For use in tightening all socket set screws.
1	Jacket Strip Blade	For use in "B" housing to peel away jacket from aluminum sheath.
1	U-Bend Spring Washer	For optional use in cases where cable variations cause JSB to come in contact with aluminum sheath. The spring washer stored under the 5/8" screw head may be installed under the JSB.

IMPORTANT NOTE: In order to validate warranty and maintain optimum tool performance, it is necessary to replace *all* of the button head screws each time the blade is replaced.

Ben Hughes Communication Products Company
207 Middlesex Avenue
P.O. Box 373
Chester, CT 06412 USA

Email: toolmaker@cableprep.com Website: www.cableprep.com

Tel: (860) 526-4337 • Fax: (860) 526-2291 • Toll Free: 1-800-394-4046